

# Interchangeable Ratcheting Crimper Series



- Made from high quality carbon steel with black oxide finish for corrosion resistance and durability
- Energy saving ratcheting mechanism requires less handle force and ensures the crimping quality
- Safety crimp release helps eliminate rejected terminations due to incorrect positioning
- Ergonomically shaped non-slip handles for user comfort
- Interchangeable die sets for wide range of applications

## CP-336F Lunar Crimp Frame

AISI 4140 Alloy steel  
HRC: 43±2

S45C medium carbon steel  
HRC: 45±3

Compact size for easy operation



Ratcheting release trigger  
(8.5" 220mm)  
Individual packing: Blister card

## CP-371 CrimpPro Crimp Frame

Change die with thumbscrews.

**30% force saving**  
Ratcheting force-saving design



Ratcheting release trigger

(9" 236mm)  
Individual packing: Blister card

- Right angled head design prevents awkward wrist bending during operation
- Interchangeable die with thumbscrew

Replacement die set	DIE Set	Crimp die profile	Application	Crimp Size	Terminals
<b>Modular Plug</b>					
CP-236DM5			Molex 8P8C/RJ45 plug & cable O/D around ø5.2 mm		
1PK-3003D11			8P8C/RJ45 keyed modular plugs (excluding AMP)		
1PK-3003D12			6P2C/6P4C/6P6C RJ11/RJ12 modular plugs		
1PK-3003D13			6P2C/6P4C/6P6C RJ11/RJ12 DEC MMJ modular plugs with an offset release tab		
1PK-3003D14			AMP 8P8C/RJ45 modular plugs. Primary strain relief crimp bar is located further back on die/modular plugs		
1PK-3003D16			RJ22 4P2C/4P4C handset modular plugs		
1PK-3003D17			Usable for RJ50, 10 position modular plugs		
1PK3003D17-MA			8P8C/RJ45 keyed or non-keyed modular plugs (excluding AMP)		
1PK-3003D25			8P8C/RJ45 WE/SS modular plugs and RG6/ RG6 Quad shield CATV "F" connectors	8P8C/RJ45 WE/SS modular plugs HEX .324", .360" HEX 8.23, 9.14 mm	
<b>Coaxial Connectors</b>					
CP-336DA4			RG58, RG59, RG62, RG174	HEX .068", .187", .213", .255" HEX 1.73, 4.75, 5.41, 6.48 mm	
CP-336DC			RG58, RG59, RG62, RG6	HEX .068", .213", .256", .319" HEX 1.73, 5.41, 6.50, 8.10 mm	
CP-336DC1			RG58, RG59, RG62, RG6	HEX .068", .216", .324", .360" HEX 1.73, 5.49, 8.23, 9.14 mm	
CP-336D1			RG58, RG59, RG6, RG174	HEX .067", .093", .211", .255", .315" HEX 1.70, 2.36, 5.36, 6.48, 8.00 mm	
CP-336DP1			For crimping RG type cables 55, 58, 59, 5, 6, 21, 141, 142, 143, 210, 212, 222, 223, 303, 304, 400 Belden: 8279, 8281, 9231 & 9141	HEX .068", .098", .213", .255", .321" HEX 1.73, 2.49, 5.41, 6.48, 8.15 mm	

Replacement die set	DIE Set	Crimp die profile	Application	Crimp Size	Terminals
CP-336DY1			RG58 (oval type)	RND .069", .218" RND 1.75, 5.54 mm	
1PK-3003D3			Cambridge CP-88, CP-89 BNC/TNC coax connectors with RG58, RG59, RG62/AU cables	SQ .068", HEX .228", .305" SQ 1.73, HEX 5.79, 7.75 mm	
1PK-3003D6			N-Series and RG8, RG11 Connectors	HEX .080", .100", .429" HEX 2.03, 2.54, 10.90 mm	
1PK-3003D8			RG58, RG6, RG174, Belden type RG8281 cables	HEX .068", .178", .324" HEX 1.73, 4.52, 8.23 mm	
1PK-3003D9			Plenum and teflon cables, RG58, RG59	HEX .042", .068", .190", .213" HEX 1.07, 1.73, 4.83, 5.41 mm	
1PK-3003D10			RG59, RG6, RG8281, F-type CATV Connectors	HEX .255", .320", .350" HEX 6.48, 8.13, 8.89 mm	
1PK-3003D22			AMP RG58 dual crimp BNC/TNC connectors	RND .049", .218" RND 1.24, 5.54 mm	
1PK-3003D28			HDTV true 75-ohm BNC/TNC coaxial connectors; Belden 1855A, 1865A, 1505A, 1505F, 1694A, 1694F	SQ .041", HEX .068", .178", .255", .278" SQ 1.04, HEX 1.73, 4.52, 6.48, 7.06 mm	
1PK-3003D30			HDTV BNC/TNC 3-piece coaxial connectors	SQ .042", HEX .197", .278" SQ 1.07, HEX 5.00, 7.06 mm	
1PK-3003D31			HDTV true 75-ohm BNC/TNC coaxial connectors, RG6, Belden 1694 & 1694A	SQ .042", HEX .068", .275", .278" SQ 1.07, HEX 1.73, 6.99, 7.06 mm	
1PK-3003D32			HDTV true 75-ohm BNC/TNC and CATV "F" coaxial connectors, RG59, RG6, Belden 8281, 1694A & 1505A	SQ .042", .052", HEX .068", .255", .324" SQ 1.07, 1.32, HEX 1.73, 6.48, 8.23 mm	
1PK-3003D33			HDTV BNC/TNC 3-piece coaxial connectors	SQ .042", HEX .178", .275" SQ 1.07, HEX 4.52, 6.99 mm	
1PK-3003D34			HDTV SMA true 75-ohm BNC/TNC and mini UHF RG174, RG59/62, mini coaxial and Belden 1855A	SQ .042", HEX .068", .178", .197", .255" SQ 1.07, HEX 1.73, 4.52, 5.00, 6.48 mm	